
InTemp AN INMARK BRAND

Fortis®

75 – 39.9L Frozen Shipper



Orange indicates solid initial condition (PCM-21)

PACKING INSTRUCTIONS

1. Remove the Lid and Bottles from the Cooler.
2. Condition Bottles, per the Conditioning Instructions.
3. Discard Foam Insert used in the Fortis 27.7L.
4. Place (2) 2086cc Bottles into Cooler.
5. Add the filled and sealed Product Carton above the Bottle.
6. Place (1) LDPE Foam End Block on each end of the Product Carton.
7. Place (1) 2086cc Bottle on each end of the Product Carton.
8. Place (2) 2086cc Bottles on each side of the Product Carton.
9. Add (2) 2086cc Bottles on top of the Product Carton.
10. Place the Lid back on the Cooler.
11. Close and Seal the Outer Carton for shipment.

PRODUCT INFORMATION SHEET

PART NUMBER

39356

BILL OF MATERIALS

QTY	Part Description
1	Corrugated Shipping Carton
1	Corrugated Product Carton
1	EPS Cooler and Lid
2	LDPE Foam End Blocks
1	LDPE Foam Insert (only use in Fortis 27.7L)
10	2086cc Bottle Assembly (PCM-21C - Orange)

SYSTEMS SPECIFICATIONS

Outside Dimensions - Shipping Carton

(mm) 641 x 552 x 502
(in) 25.3 x 21.8 x 19.8

Inside Dimensions – Product Space

(mm) 425 x 321 x 292
(in) 16.75 x 12.63 x 11.50

Dimensions – Bottles

(mm) 337 x 235 x 32
(in) 13.25 x 9.25 x 1.25

Payload Volume

(liters) 39.9
(in^3) 2435

Dead Weight (Includes Refrigerant)

(kg) 23.6
(lb) 52.11

CONDITIONING INSTRUCTIONS

PCM -21C (shown in Orange)


Freeze PCM-21 solid in -30°C environment. Individual pieces will require 2-3 days, cases up to a week, and pallets of bottles 2-3 weeks, depending on equipment capabilities and other variables.

Inmark

Inmark Headquarters - USA ■ Inmark Europe BV - Netherlands ■ Inmark SG Pte. Ltd. - Singapore
+1(770) 373-3300 +31 (0)162 748 100 +65 6861 7108
Sales@InmarkPackaging.com ■ InmarkPackaging.com


CPI 18-0328-B Rev.0

Summer



Reached -15°C at 59.33 hours

Summer



Reached -15°C at 60.58 hours